



6" 520 TVL Network High Speed Dome

Mode: WHB-5206P

- 1/4" SONY CCD
- 520 TVL Horizontal Resolution
- H.264 video codec
- $\pm 0.1^\circ$ preset accuracy
- 540°/s pan preset speed and 400°/s tilt preset speed
- 360° endless pan range and -5°-185° tilt range
- Weather Proof: IP66 standard

Specifications

| | | |
|----------------------------|---------------------------|---|
| Camera | Image Sensor | 1/4" Sony CCD |
| | Effective Pixel | PAL:752(H)×582(V) NTSC:768(H)×494(V) |
| | Horizontal Resolution | 520 TVL |
| | Signal System | PAL /NTSC |
| | Min.Illumination | 0.1Lux/F1.6 |
| | White Balance | Auto / Manual / ATW |
| | AGC | Auto / Manual |
| | S / N Ratio | >50dB |
| | BLC | On / Off |
| | Electronic Shutter | PAL:1/50~1/10,000s NTSC:1/60~1/10,000s |
| | Day/Night | ICR |
| | Focus Model | Auto/ Manual |
| Images | Max. Image Resolution | PAL:704×576 NTSC:704×480 |
| | Frame Rate | PAL :25 fps (704×576) NTSC: 30 fps (704×480) |
| Media Compression Standard | Video Compression | H.264/ MPEG-4/MJPEG |
| | Audio Compression | OggVorbis |
| Pan and Tilt | Pan Range | 360°endless |
| | Pan Speed | Pan Manual Speed: 0.1°~300°/s, Pan Preset Speed: 540°/s |
| | Tilt Range | -5°~185°(Auto Flip) -5°~185°(Auto Mirror) |
| | Tilt Speed | Tilt Manual Speed: 0.1°~240°/s, Tilt Preset Speed: 400°/s |
| | Number of Preset | 256 |
| | Patrol | 8 patrols, each patrol up to 32 presets |
| | Pattern | 4 patterns, with the total recording time not less than 10 min |
| | Power-off Memory | Support |
| | Park Action | Preset / Patrol / Pattern / Pan scan / Tilt scan / Random scan / Frame scan / Panorama scan |
| | PTZ Position Display | On / Off |
| Alarm | Alarm Input | 1 input |
| | Alarm Output | 1 relay output |
| | Alarm Actions | Preset, Patrol, Pattern, SD card recording, Relay output, Notification on Client |
| Input/ Output | Monitor Output | 1.0V[p-p] / 75Ω, BNC |
| | Audio input | LINE input |
| | Audio Output | Line level, |
| Network Protocols | Ethernet | TCP/IP, HTTP, FTP, DHCP, DNS, RTP / RTCP, PPPoE , SMTP, NTP, SNMP |
| | RS485 | Pelco-P, Pelco-D |
| Functions | No. of Simultaneous Users | Up to 6 users |

| | | |
|------------|------------------------|---|
| | Dual Streams | Support |
| | Local storage | SD/SDHC support |
| Client GUI | Camera Control | Pan / Tilt, Zoom, Focus, Click centering, Drag zoom, Iris, Preset position call and program, Auto mode. |
| | OSD | Support |
| | Date Display | Support |
| | Patrol Message Display | Support |
| General | Menu Language | English, Chinese |
| | Power Supply | 12V DC o |
| | Power Consumption | 15W max |
| | Protection Level | IP66 standard |
| | EMS protection | TVS 3000V lightning protection, surge protection and voltage transient protection |