


2. Stand IP camera

 <p>VGA CMOS-based Vandal Proof Network Dome Camera</p>	<p>Model: WH_0M3BMS_(P)</p> <ul style="list-style-type: none"> ● VGA(640x480)Pixels Image resolution ● Progressive scan CMOS ● H.264/MPEG-4 video compression with high compression ratio ● Dual Streams ● Up to 32 GB SD/SDHC card local storage ● Two-way audio ● PoE is Optional
--	---

Specifications

Camera	Image Sensor	1/4" Progressive CMOS
	Min. Illumination	Color: 0.2Lux @ F1.2 B/W: 0.02Lux @ F1.2
	Electronic Shutter	1/25s~1/100,000s
	Lens Mount	CS
Media Compression Standard	Video Compression	H.264/ MPEG-4/MJPEG
	Audio Compression	OggVorbis
	Bit rate	32 Kbps~16Mbps
Image	Max. Image Resolution	640×480
	Frame Rate	50HZ: 25fps (640×480) 60HZ: 30fps (640×480)
	Video Parameter	Saturation, Brightness, Contrast adjustable through client software or web browser
Network Protocol	Protocols	TCP/IP, HTTP, FTP, DHCP, DNS, DDNS, RTP/RTSP, PPPoE, SMTP, NTP
Interface	Ethernet Interface	1 RJ45 10M / 100M self-adaptive
	RS485 Interface	1 RS-485 interface
	Intelligent Alarm	Motion Detection, Video Loss, Network Disconnect, IP conflict, Storage exception
	Alarm Input	1 channel
	Alarm Output	1 channel
	Audio Input	1 channel
	Audio Output	1 channel (Line level, 600Ω)
	Video Output	1Vp-p Composite Output (75Ω/RCA)
	Local Storage	Support SD/SDHC
	Basics	Reset button, Anti-flicker, Dual Stream, Heartbeat, Password Protection
General	Operating Condition	-10°C~60°C Humidity 90% or less
	Power Supply	DC12V±10%
	Power Consumption	4.5W MAX
Optional	PoE	(Power over Ethernet)