



1.3 Megapixel  
 CCD-based Vandal Proof  
 Network Dome Camera

**Model: WH\_1M3BPS\_(P)**

- 1/3" SONY progressive scan CCD
- Up to 1280×960 pixels Image resolution
- H.264/MPEG-4 video compression with high compression ratio
- Dual Streams
- Up to 32 GB SD/SDHC card local storage
- Auto switch ICR Filter
- Two-way audio
- PoE is optional

**Specifications**

Camera	Image Sensor	1/3 " SONY progressive scan CCD
	Effective Pixels	1280 (H) × 960 (V)
	Min. Illumination	0.1Lux @ F1.2 (Color) 0.01Lux @ F1.2 (B/W)
	Auto Iris	DC Drive
	Day/Night	IR cut filter with auto switch
Media Compression Standard	Video Compression	H.264/ MPEG-4/MJPEG
	Audio Compression	OggVorbis
	Video Bit Rate	32Kbps~8Mbps
Image	Max. Image Resolution	1280 × 960
	Frame Rate	50Hz:12.5fps(1280×960),25fps(1280×720) 60Hz:12.5fps(1280×960),24fps(1280×720)
Network Protocol	Protocols	TCP/IP, RTP/RTCP, FTP, HTTP, DHCP, DNS, PPPoE (SMTP, NTP, SNMP optional)
Interface	Ethernet Interface	1 RJ45 10M / 100M self-adaptive
	RS485 Interface	1 RS-485 interface
	Intelligent Alarm	Motion Detection, Video Loss, Network Disconnect, IP conflict, Storage exception
	Alarm Input	1 channel input
	Alarm Output	1 channel relay output
	Audio Input	1 channel
	Audio Output	1 channel (Line level, 600Ω)
	Video Output	1Vp-p Composite Output (75Ω/BNC)
	Local Storage	Support SD/SDHC
	Basics	Reset button, Anti-flicker, Dual Stream, Heartbeat, Password Protection
General	Power Supply	12VDC±10%
	Power Consumption	5W (10W with ICR working)
	Working Temperature	-10°C~60°C
	Weather Proof	IP66
	Impact Protection	IEC60068-2-75Eh,50J; EN50102, up to IK10
Optional	PoE	PoE (Power over Ethernet)