



5 Megapixel CMOS-based Network Camera

Model: WH\_5MOGMS\_(P)(W)

- Up to 5 Megapixel Image resolution
- Progressive scan CMOS
- H.264/MPEG-4 video compression with high compression ratio
- Dual Streams
- Up to 32 GB SD/SDHC card local storage
- Auto switch ICR Filter
- Two-way audio
- PoE and WiFi optional

### Specifications

Camera	Image Sensor	1/2.5" Progressive Scan CMOS
	Min. Illumination	Color: 0.6Lux @ F1.2 B / W: 0.08Lux @ F1.2
	Electronic Shutter	1/25s ~1/20,000s
	Lens Mount	C/CS mount
	Auto Iris	DC Drive
	Day / Night	IR cut filter with auto switch
Media Compression Standard	Video Compression	H.264/ MPEG-4/MJPEG
	Audio Compression	OggVorbis
	Bit rate	32 Kbps~16Mbps
Image	Max. Image Resolution	2560×1920
	Frame Rate	50Hz: 6fps(2560×1920), 12.5fps(2048×1536), 25fps(1920×1080), 25fps(1600×1200), 25fps(1280×720) 60Hz: 7.5fps(2560×1920), 15fps(2048×1536), 30fps(1920×1080), 30fps(1600×1200), 30fps(1280×720)
	Image Settings	Saturation, Brightness, Contrast adjustable through client software or web browser
Network Protocol	Protocols	TCP/IP,HTTP,DHCP,DNS,DDNS,RTP/RTSP, PPPoE, SMTP, NTP(SNMP, HTTPS,FTP)
Interface	Ethernet Interface	1 RJ45 10M / 100M self-adaptive
	RS485 Interface	1 RS-485 interface
	Intelligent Alarm	Motion Detection, Video Loss, Network Disconnect, IP conflict, Storage exception
	Alarm Input	1 channel
	Alarm Output	1 channel
	Video Output	1Vp-p Composite Output (75Ω/BNC)
	Audio Input	1 channel microphone input
	Audio Output	1 channel audio interface (Line level, 600Ω)
	Local Storage	Support SD/SDHC
	Basics	Reset button, Anti-flicker, Dual Stream, Heartbeat, Password Protection
General	Operating Condition	-10°C~60°C(14°F~140°F), Humidity 90% or less(non-condensing)
	Power Supply	DC12V±10% / PoE (AC24V optional)
	Power Consumption	5W MAX(10W MAX with ICR Working)
Options	WiFi	802.11b/g is Optional
	PoE	Power Over Ethernet is Optional